



30.000 h | 175-250V-50-60Hz | 0.90 | 220° | Ra ≥ 80 | SDCM < 6 | < 0,5s starting time | Warm-up Time < 0,5s | IP 65 | IK 08 | Hg Free | Pb Free | FREE | CE

| Ordercode | Power | CCT | luminous flux | max intensity | EAN13 | Laser Optical Reading |
|------------|-------|-------|---------------|---------------|---------------|-----------------------|
| TRI-6020C | 20W | 3000K | 1800lm | 400cd | 8033638773611 | |
| TRI-6020D | 20W | 4200K | 1900lm | 400cd | 8033638773628 | |
| TRI-6020F | 20W | 6400K | 1900lm | 400cd | 8033638773635 | |
| TRI-12040C | 40W | 3000K | 3400lm | 800cd | 8033638772096 | |
| TRI-12040D | 40W | 4200K | 3500lm | 800cd | 8033638772102 | |
| TRI-12040F | 40W | 6400K | 3500lm | 800cd | 8033638772119 | |
| TRI-15050C | 50W | 3000K | 4300lm | 1000cd | 8033638772126 | |
| TRI-15050D | 50W | 4200K | 4400lm | 1000cd | 8033638772133 | |
| TRI-15050F | 50W | 6400K | 4400lm | 1000cd | 8033638772140 | |

Easy'n Fast Link System



Inner Box _ 1 pcs

| EAN13 | Laser Optical Reading |
|-----------|-----------------------|
| TRI-6020C | 8033638773611 |
| TRI-6020D | 8033638773628 |
| TRI-6020F | 8033638773635 |

| | |
|------------|---------------|
| TRI-12040C | 8033638772096 |
| TRI-12040D | 8033638772102 |
| TRI-12040F | 8033638772119 |

| | |
|------------|---------------|
| TRI-15050C | 8033638772126 |
| TRI-15050D | 8033638772133 |
| TRI-15050F | 8033638772140 |

Outer Box _ 4 pcs

| EAN13 | Laser Optical Reading |
|-----------|-----------------------|
| TRI-6020C | 8033638777817 |
| TRI-6020D | 8033638777824 |
| TRI-6020F | 8033638777831 |

L.71cm _ H.15cm _ P.17cm - Kg 4

| | |
|------------|---------------|
| TRI-12040C | 8033638778791 |
| TRI-12040D | 8033638777749 |
| TRI-12040F | 8033638779545 |

L.127cm _ H.15cm _ P.17cm - Kg 7

| | |
|------------|---------------|
| TRI-15050C | 8033638778807 |
| TRI-15050D | 8033638778814 |
| TRI-15050F | 8033638779538 |

L.155cm _ H.15cm _ P.17cm - Kg 8