



30.000 h | 175-250V-50-60Hz | 0.90 | 220° | Ra ≥ 80 | SDCM < 6 | < 0,5s starting time | Warm-up Time < 0,5s | IP 65 | IK 08 | Hg Free | Pb Free | FREE | CE

Ordercode	Power	CCT	luminous flux	max intensity	EAN13	Laser Optical Reading
TRI-6020C	20W	3000K	1800lm	400cd	8033638773611	
TRI-6020D	20W	4200K	1900lm	400cd	8033638773628	
TRI-6020F	20W	6400K	1900lm	400cd	8033638773635	
TRI-12040C	40W	3000K	3400lm	800cd	8033638772096	
TRI-12040D	40W	4200K	3500lm	800cd	8033638772102	
TRI-12040F	40W	6400K	3500lm	800cd	8033638772119	
TRI-15050C	50W	3000K	4300lm	1000cd	8033638772126	
TRI-15050D	50W	4200K	4400lm	1000cd	8033638772133	
TRI-15050F	50W	6400K	4400lm	1000cd	8033638772140	

Easy'n Fast Link System



Inner Box \_ 1 pcs

EAN13	Laser Optical Reading
TRI-6020C	8033638773611
TRI-6020D	8033638773628
TRI-6020F	8033638773635

TRI-12040C	8033638772096
TRI-12040D	8033638772102
TRI-12040F	8033638772119

TRI-15050C	8033638772126
TRI-15050D	8033638772133
TRI-15050F	8033638772140

Outer Box \_ 4 pcs

EAN13	Laser Optical Reading
TRI-6020C	8033638777817
TRI-6020D	8033638777824
TRI-6020F	8033638777831

L.71cm \_ H.15cm \_ P.17cm - Kg 4

TRI-12040C	8033638777891
TRI-12040D	8033638777749
TRI-12040F	8033638779545

L.127cm \_ H.15cm \_ P.17cm - Kg 7

TRI-15050C	8033638778807
TRI-15050D	8033638778814
TRI-15050F	8033638779538

L.155cm \_ H.15cm \_ P.17cm - Kg 8